

KEYLIGHTING

North Brook Works, Alkincote Street, Keighley, BD21 5JT Tel: 01535 616 300 Fax: 01535 616 301
 Email: sales@keylighting.co.uk Web: www.keylighting.co.uk



Construction & Assembly

A range of compact fluorescent downlighters, with super slim profile which allows installation into the shallowest recess. Two versions available both feature an all polycarbonate housing and gearbox. A unique trap-door on the body gives access to the lamps for ease of maintenance and installation.

Packing

Fittings are individually boxed, but box size is dependent on gear choice.

Installation

Fittings are suitable for any ceiling type and the units are held in the ceiling by means of side screws accessed from inside the fitting by unclipping the diffuser. All lamps are horizontally mounted in this luminaire.

Accessories

IP Available with a mid glass which seals the fitting to IP44

Available in Switch Start, High Frequency and High Frequency Dimmable (only available in Flex) and the option of integral 3 hour emergency to give 10% of fittings light output.

Dimensions and Range

Range	Lamps	Lumens per			Dimensions (mm)		
		Lamp	Fitting	Watts	Cut Out	O/D	Height
DL-FLEX-2x18	2 x 18 W PLC	1200	2400	48.0	190	205	130
DL-FLEX-2x18-HF	2 x 18 W PLC	1200	2400	37.5	190	205	130
DL-FLEX-2x26	2 x 26 W PLC	1800	3600	64.4	190	205	130
DL-FLEX-2x26-HF	2 x 26 W PLC	1800	3600	51.0	190	205	130
DL-HELIX-2x10/13	2 x 10 or 13 W PLC	600 / 900	1200 / 1800	20/26	160	170	110
DL-HELIX-2x10/13-HF	2 x 10 or 13 W PLC	600 / 900	1200 / 1800	20/26	160	170	110