

KEYLIGHTING

North Brook Works, Alkincote Street, Keighley, BD21 5JT Tel: 01535 616 300 Fax: 01535 616 301
 Email: sales@keylighting.co.uk Web: www.keylighting.co.uk



General

Our NON CORROSIVE is suited to industrial lighting applications. Available in either polycarbonate or acrylic all with glass reinforced bodies. Switch Start, high frequency & integral emergency options are available & the new T5 high efficiency & high output lamps available in a more compact housing.

Construction

The body is made from glass reinforced polymer & diffusers are either poly carbonate or acrylic. All luminaries have pressed steel gear trays & all parts required for sealing & mounting the fittings. Assembly.

All units are 100% tested prior to packing & shipping.

Accessories

Stainless steel clips available on request

Additional Extras Available

EM Integral emergency on one lamp to maintain the lamp at approximately 10 % of its normal output for 3 hours.

EM-ST A self testing emergency system which monitors the condition of Batteries, lamp & supply. Automatically tests the lamps in accordance with regulations.

HFD This special control gear designed to allow the lamps to be dimmed in various ways. Can be controlled by ambient light level presence of people, or with a IR hand held device. These systems can be linked to computers for total lighting control in a building.

Dimensions & Range

Range	Tube & Wattage	Lumens Per		Watts		Dimensions (mm)		
		Lamp	Fitting	S/Start	High Freq	Height	Width	Length
NC4	1 x 36 W T8	2850	2850	48.0	37.4	100	100	1270
NC5	1 x 58 W T8	4600	4600	74.4	57.0	100	100	1570
NC6	1 x 70 W T8	5800	5800	88.8	70.4	100	100	1834
NC24	2 x 36 W T8	2850	5700	96.0	76.5	100	160	1270
NC25	2 x 58 W T8	4600	9200	148.8	112.0	100	160	1570
NC26	2 x 70 W T8	5800	11600	177.6	135.5	100	160	1834
NC128	1 x 28 W T5	2600	2600	N/A	31.5	72	59	1220
NC135	1 x 35 W T5	3300	3300	N/A	39.0	72	59	1510
NC228	2 x 28 W T5	2600	5200	N/A	63.0	74	100	1220
NC235	2 x 35 W T5	3300	6600	N/A	77.5	74	100	1510